

MDT Room Temperature Controller Smart 63, Studio white glossy finish


With colour display, temperature/humidity sensor and 4 inputs

Version		
SCN-RTR63S.01	Room Temperature Controller Smart 63	To fit 63mm systems/ranges, studio white glossy finish

The MDT Room Temperature Controller Smart 63 with integrated temperature and humidity sensor is used for indoor room temperature regulation. Switch Actuators/Heating Actuators with electrothermic valves or motorized KNX actuators can be controlled by the Room Temperature Controller.

Set/actual temperature, relative/absolute humidity, outside temperature and time are displayed on the active color display. Additionally the Room Temperature Controller Smart 63 has 4 binary inputs to connect potential free contacts. The inputs can be used for direct connection of window contacts, buttons/switches for lighting control or blind control. The length of connection cables is 22cm

The MDT Room Temperature Controller Smart 63 is a flush mounted device for fixed installations in dry rooms. For project design and commissioning of the Room Temperature Controller Smart 63 it is recommended to use the ETS. Please download the application software at www.mdt.de/downloads.html



- Production in Germany, certified according to ISO 9001
- Fits 63mm systems/ranges, e.g.:
 - Busch-Jaeger future linear, solo, carat, Busch-axent
- **Active colour display to indicate function and status**
- **Background colour w/b and display brightness adjustable**
- **Display of set and actual temperature**
- **For indoor temperature controlling**
Range -10 to +50°C
- **Selectable temperature controller (PI, Two-position, PWM)**
- Simple setpoint adjustment via separate +/- buttons
- 1Bit +/-, 1Byte oder 2Byte absolute object for setpoint adjustment
- Setpoint values are stored at bus voltage failure
- Limit values min/max, frost protection alarm, min/max memory
- Operation mode can be set via Bit/Byte objects
- **Temperature and humidity sensor with dew point calculation**
- Message when leaving the comfort zone
- **4 binary inputs to connect potential free contacts (push-buttons or window/auxiliary contacts)**
- Ventilation control by hand or automatic operation
- 14Byte object for plain text diagnostic
- Installation in a installation box with included support ring
Recommended installation height: 1,6m
- Integrated bus coupling unit, 3 years warranty

Technical Data	SCN-RTR63S.01		
Measurement range temperature sensor	-10 to + 50°C		
Measurement range humidity sensor	0 - 95%*		
Number of inputs	4 (for potential free contacts)		
Internal contact voltage	3,3VDC** internal		
Recommended installation height	1,60m		
Specification KNX interface	TP-256		
Available application software	ETS 5		
Permitted wire gauge			
KNX busconnection terminal	0,8mm Ø, solid core		
Power supply	KNX bus		
Power consumption KNX bus typ.	<0,3W		
Permitted input cable length	10m		
Operation temperature range	0 to + 45°C		
Ambient humidity (permanent)	20 - 80%		
Ambient humidity (short-term)	0 - 95%		
Enclosure	IP 20		
Dimensions (W x H)	63mm x 63mm		
Installation depth in installaton box	12mm		

* Avoid condensation

** There is no galvanic separation between contact voltage and KNX bus voltage.

Exemplary circuit diagram SCN-RTR63S.01

